USB-120 / USB-300 Driver Installation Guide

• **package contains:**
1. Install CD.
2. USB toRS232 adaptor.
3. Install manual.

• **System Required:**
Windows 95/98/2000NT 4.0/XP or above.

• **Hardware Required:**
PC or Laptop with USB port

• **Install THERMOLINK:**
1. We recommend close all other application before installing driver.

2. We recommend not plug connector to USB port before installation.

3. Insert setup CD disk to CD disk drive, installation will execute automatically. If not, execute "**start**"→"**run**", and edit X:\SETUP(X is your disk drive), then click OK button, installation will start.

4. While installing, it will show this window below, just click "**next**" to continue.

CP2102_xp2k InstallShield Wizard

Welcome to the InstallShield Wizard for
CP2102_xp2k

The InstallShield(R) Wizard will install CP2102_xp2k on your computer. To continue, click Next.

5. When this window below appear, please plug in the connector to USB port, installation will confirm the device.

Plug in the hardware

The installer has detected that the hardware associated with this package is not currently plugged-in to the computer. Please plug in the hardware associated with this package after the installation has completed successfully.

OK

6. After finish installation, execute "**start**" → "**My Computer**", then choose "View System Information" on the left top of the window, the window below will show up:

7. Choose "**Hardware**" option and click "**Device Manager**" button, click "**+**" symbol on the left side of Ports(COM &LPT), if the device "**CP2101 USB to UART Bridge Controller(COMx)**" is in the list, the connector is ready to work.

Device Manager
File Action View Help

Ports (COM & LPT)
  Communications Port (COM1)
  Communications Port (COM2)
  CP2101 USB to UART Bridge controller (COM3)
  ECP Printer Port (LPT1)
Processors
Sound, video and game controllers
Storage volumes
System devices
Universal Serial Bus controllers